

Table of Contents

Protokolle	1
Interfaces	2
Klassen	4
Unit Tests	6

Alle unsere Objective-C Klassen verwenden einen einheitlichen Style.

Protokolle

Für Protokolle verwenden wir folgenden Style:

ProtocolTemplate

```
/*
 * Copyright 2018 SIB Visions GmbH
 *
 * Licensed under the Apache License, Version 2.0 (the "License"); you
 may not
 * use this file except in compliance with the License. You may obtain
 a copy of
 * the License at
 *
 * http://www.apache.org/licenses/LICENSE-2.0
 *
 * Unless required by applicable law or agreed to in writing, software
 * distributed under the License is distributed on an "AS IS" BASIS,
 WITHOUT
 * WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See
 the
 * License for the specific language governing permissions and
 limitations under
 * the License.
 *
 *
 * History
 *
 * dd.MM.yyyy - [XX] - creation
 */

/*!
 @protocol Foo
 @abstract Protocol implemented by Bar.
 @discussion That's what they do.
 */
@protocol Foo

#pragma mark -
#pragma mark Required

/*!
 @method requiredMethod:
 @abstract Validates the specified item.
 @param pItem The item to be validated.
 */
- (void)requiredMethod:(id) pItem;
```

```
/*!
 * @method anotherRequiredMethod:
 * @abstract Applies validation rules.
 */
- (void)anotherRequiredMethod;

#pragma mark -
#pragma mark Optional

@optional

/*!
 * @method anOptionalMethod:
 * @abstract Checks optional things.
 */
- (void)anOptionalMethod;

/*!
 * @method anotherOptionalMethod:
 * @abstract Checks another optional things.
 */
- (void)anotherOptionalMethod;

@end
```

Folgende Regeln werden durch diese Vorlage definiert:

- Zuerst werden die erforderlichen Methoden definiert
- danach alle optionalen Methoden
- Gruppierung mit #pragma mark ...
- Im Header erstellen wir bei wichtigen Änderungen einen Hinweis mit Zeitstempel und Autor
- Dokumentation für die Protokoll Deklaration und alle Methoden

Interfaces

Für Interfaces (.h files) verwenden wir folgenden Style:

InterfaceTemplate

```
/*
 * Copyright 2018 SIB Visions GmbH
 *
 * Licensed under the Apache License, Version 2.0 (the "License"); you
 may not
 * use this file except in compliance with the License. You may obtain
 a copy of
 * the License at
 *

```

```
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See
the
* License for the specific language governing permissions and
limitations under
* the License.
*
*
* History
*
* dd.MM.yyyy - [XX] - creation
*/

#import "Bar.h"

/*!
    @class Foo
    @abstract Foo provides a UI element.
    @discussion A Foo object is a simple view that can do two things:
    Jump, Run.
    */
@interface Foo : Bar
{
    #pragma mark -
    #pragma mark Instance variable declarations

    @private

    /*! @var value the value of foo. */
    float value;
}

#pragma mark -
#pragma mark Property declarations

/*! @property value the value property. */
@property float value;

#pragma mark -
#pragma mark Initialization

/*!
    @method initWithString:
    @abstract Creates a new foo with string representation of width and
    height.
    @param pString the width and height
    @result a new Foo instance.
```

```

*/
- (id)initWithString:(NSString *)pString;

#pragma mark -
#pragma mark Method declarations

/*!
 @method concatWidth:height:
 @abstract Concatenates the width and height.
 @param pWidth the width.
 @param pHeight the height.
 @result the string representation.
*/
+ (NSString *)concatWidth:(float)pWidth height:(float):pHeight;

/*!
 @method setWidth:height:
 @abstract Sets the foo width and height.
 @param pWidth the width.
 @param pHeight the height.
*/
- (void)setWidth:(float)pWidth height:(float)pHeight;

@end

```

Folgende Regeln werden durch diese Vorlage definiert:

- Gruppierung mit #pragma mark ...
- Im Header erstellen wir bei wichtigen Änderungen einen Hinweis mit Zeitstempel und Autor
- Dokumentation für die Klassen Deklaration, ALLE Methoden, Properties und Variablen

Klassen

Für Klassen (.m files) verwenden wir folgenden Style:

ClassTemplate

```

/*
 * Copyright 2018 SIB Visions GmbH
 *
 * Licensed under the Apache License, Version 2.0 (the "License"); you
 may not
 * use this file except in compliance with the License. You may obtain
 a copy of
 * the License at
 *
 * http://www.apache.org/licenses/LICENSE-2.0
 *
 * Unless required by applicable law or agreed to in writing, software

```

```
* distributed under the License is distributed on an "AS IS" BASIS,  
WITHOUT  
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See  
the  
* License for the specific language governing permissions and  
limitations under  
* the License.  
*  
*  
* History  
*  
* dd.MM.yyyy - [XX] - creation  
*/  
  
#import "Foo.h";  
  
@implementation Foo  
  
#pragma mark -  
#pragma mark Properties  
  
@synthesize value;  
  
#pragma mark -  
#pragma mark Initialization  
  
- (id)initWithString:(NSString *)pString  
{  
    ...  
}  
  
#pragma mark -  
#pragma mark Method declarations  
  
+ (NSString *)concatWidth:(float)pWidth height:(float)pHeight  
{  
    ...  
}  
  
- (void)setWidth:(float)pWidth height:(float)pHeight  
{  
    ...  
}  
  
@end
```

Folgende Regeln werden durch diese Vorlage definiert:

- Gruppierung mit #pragma mark ...

- Im Header erstellen wir bei wichtigen Änderungen einen Hinweis mit Zeitstempel und Autor

Unit Tests

Als Testing Framework kommt OCUit zum Einsatz.

Für Unit Tests verwenden wir folgenden Style:

TestTemplate

```
/*
 * Copyright 2018 SIB Visions GmbH
 *
 * Licensed under the Apache License, Version 2.0 (the "License"); you
 may not
 * use this file except in compliance with the License. You may obtain
 a copy of
 * the License at
 *
 * http://www.apache.org/licenses/LICENSE-2.0
 *
 * Unless required by applicable law or agreed to in writing, software
 * distributed under the License is distributed on an "AS IS" BASIS,
 WITHOUT
 * WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See
 the
 * License for the specific language governing permissions and
 limitations under
 * the License.
 *
 *
 * History
 *
 * dd.MM.yyyy - [XX] - creation
 */

#import "Foo.h"

@implementation FooTest

#pragma mark -
#pragma mark Internal methods

#pragma mark -
#pragma mark Test methods

/*!
 @abstract Tests the init method.
 */
```

```
- (void)testInit
{
    ...
}

@end
```

Folgende Regeln werden durch diese Vorlage definiert:

- Gruppierung mit #pragma mark ...
- Jede Test Klasse endet mit "Test"
- Jede Test Methode beginnt mit "test"
- Im Header erstellen wir bei wichtigen Änderungen einen Hinweis mit Zeitstempel und Autor
- Dokumentation für die Klassen Deklaration und alle Test Methoden

From:

<https://doc.sibvisions.com/> - **Documentation**

Permanent link:

https://doc.sibvisions.com/de/jvx/join/style_objectivec



Last update: **2018/02/06 10:00**