

# Table of Contents

Protocols .....	1
Interfaces .....	2
Classes .....	4
Unit Tests .....	6

All of our Objective-C classes use a standardized style.

## Protocols

We use the following style for protocols:

### ProtocolTemplate

```
/*
 * Copyright 2018 SIB Visions GmbH
 *
 * Licensed under the Apache License, Version 2.0 (the "License");
 * you may not
 * use this file except in compliance with the License. You may obtain
 * a copy of
 * the License at
 *
 * http://www.apache.org/licenses/LICENSE-2.0
 *
 * Unless required by applicable law or agreed to in writing, software
 * distributed under the License is distributed on an "AS IS" BASIS,
 * WITHOUT
 * WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See
 * the
 * License for the specific language governing permissions and
 * limitations under
 * the License.
 *
 *
 * History
 *
 *
 * dd.MM.yyyy - [XX] - creation
 */

/*!
@protocol Foo
@abstract Protocol implemented by Bar.
@discussion That's what they do.
*/
@protocol Foo

#pragma mark -
#pragma mark Required

/*! 
 @method requiredMethod:
 @abstract Validates the specified item.
 @param pItem The item to be validated.
*/
- (void)requiredMethod:(id) pItem;
```

```

/*
 @method anotherRequiredMethod:
 @abstract Applies validation rules.
*/
- (void)anotherRequiredMethod;

#pragma mark -
#pragma mark Optional

(optional

/*
 @method anOptionalMethod:
 @abstract Checks optional things.
*/
- (void)anOptionalMethod;

/*
 @method anotherOptionalMethod:
 @abstract Checks another optional things.
*/
- (void)anotherOptionalMethod;

@end
```

The following rules are defined by this template:

- First, all required methods are defined
- Then all optional methods
- Grouping using the #pragma mark ...
- Important changes are documented in the header, including time stamp and author
- Documentation for the protocol declaration and all methods

## Interfaces

We use the following style for interfaces (.h files):

### [InterfaceTemplate](#)

```

/*
 * Copyright 2018 SIB Visions GmbH
 *
 * Licensed under the Apache License, Version 2.0 (the "License");
 * you may not
 * use this file except in compliance with the License. You may obtain
 * a copy of
 * the License at
 */
```

```
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See
the
* License for the specific language governing permissions and
limitations under
* the License.
*
*
* History
*
* dd.MM.yyyy - [XX] - creation
*/
#import "Bar.h"

/*! 
@class Foo
@abstract Foo provides a UI element.
@discussion A Foo object is a simple view that can do two things:
Jump, Run.
*/
@interface Foo : Bar
{
    #pragma mark -
    #pragma mark Instance variable declarations

    @private
    /*! @var value the value of foo. */
    float value;
}

#pragma mark -
#pragma mark Property declarations

/*! @property value the value property. */
@property float value;

#pragma mark -
#pragma mark Initialization

/*! 
@method initWithString:
@abstract Creates a new foo with string representation of width and
height.
@param pString the width and height
@result a new Foo instance.
```

```

*/
- (id)initWithString:(NSString *)pString;

#pragma mark -
#pragma mark Method declarations

/*! 
 @method concatWidth:height:
 @abstract Concatenates the width and height.
 @param pWidth the width.
 @param pHeight the height.
 @result the string representation.
*/
+ (NSString *)concatWidth:(float)pWidth height:(float):pHeight;

/*! 
 @method setWidth:height:
 @abstract Sets the foo width and height.
 @param pWidth the width.
 @param pHeight the height.
*/
- (void)setWidth:(float)pWidth height:(float)pHeight;

@end

```

The following rules are defined by this template:

- Grouping using the #pragma mark ...
- Important changes are documented in the header, including time stamp and author
- Documentation for the class declaration, ALL methods, properties and variables

## Classes

We use the following style for classes (.m files):

### [ClassTemplate](#)

```

/*
 * Copyright 2018 SIB Visions GmbH
 *
 * Licensed under the Apache License, Version 2.0 (the "License");
 * you may not
 * use this file except in compliance with the License. You may obtain
 * a copy of
 * the License at
 *
 * http://www.apache.org/licenses/LICENSE-2.0
 *
 * Unless required by applicable law or agreed to in writing, software

```

```
* distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See
the
* License for the specific language governing permissions and
limitations under
* the License.
*
*
* History
*
* dd.MM.yyyy - [XX] - creation
*/
#import "Foo.h";

@implementation Foo

#pragma mark -
#pragma mark Properties

@synthesize value;

#pragma mark -
#pragma mark Initialization

- (id)initWithString:(NSString *)pString
{
    ...
}

#pragma mark -
#pragma mark Method declarations

+ (NSString *)concatWidth:(float)pWidth height:(float):pHeight
{
    ...
}

- (void)setWidth:(float)pWidth height:(float)pHeight
{
    ...
}

@end
```

The following rules are defined by this template:

- Grouping using the #pragma mark ...

- Important changes are documented in the header, including time stamp and author

## Unit Tests

OCUnit is used as the testing framework.

We use the following style for unit tests:

### TestTemplate

```
/*
 * Copyright 2018 SIB Visions GmbH
 *
 * Licensed under the Apache License, Version 2.0 (the "License");
 * you may not
 * use this file except in compliance with the License. You may obtain
 * a copy of
 * the License at
 *
 * http://www.apache.org/licenses/LICENSE-2.0
 *
 * Unless required by applicable law or agreed to in writing, software
 * distributed under the License is distributed on an "AS IS" BASIS,
 * WITHOUT
 * WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See
 * the
 * License for the specific language governing permissions and
 * limitations under
 * the License.
 *
 *
 * History
 *
 * dd.MM.yyyy - [XX] - creation
 */

#import "Foo.h"

@implementation FooTest

#pragma mark -
#pragma mark Internal methods

#pragma mark -
#pragma mark Test methods

/*! 
 * @abstract Tests the init method.
 */

```

```
- (void)testInit
{
    ...
}

@end
```

The following rules are defined by this template:

- Grouping using the #pragma mark ...
- Each test class ends with “Test”
- Each test method starts with “test”
- Important changes are documented in the header, including time stamp and author
- Documentation for the class declaration and all test methods

From:

<http://doc.sibvisions.com/> - **Documentation**

Permanent link:

[http://doc.sibvisions.com/jvx/join/style\\_objectivec](http://doc.sibvisions.com/jvx/join/style_objectivec)

Last update: **2018/02/06 09:57**

