

# Table of Contents

The application itself logs messages in Javascript console of your browser (developer tools). The network tab in developer tools shows all requests, the payload and responses. This is very helpful for debugging.

If you want to know what's happening on server-side. This is not enough. The server-side runs on a Java application server like Tomcat or Wildfly. To enable logging on server-side, simply do following:

Create the directory **classes** in your applications WEB-INF folder. The folder already contains lib, rad directories and web.xml file. In the newly created classes folder, create a file **logging.properties** with following content:

### logging.properties

```
#####  
#####  
# HANDLER definition  
#####  
#####  
  
# development handlers  
#handlers = java.util.logging.ConsoleHandler  
  
# tomcat handlers  
handlers = java.util.logging.ConsoleHandler,  
org.apache.juli.FileHandler  
  
# application handlers  
#handlers = java.util.logging.FileHandler  
  
#####  
#####  
# HANDLER configuration  
#####  
#####  
  
java.util.logging.ConsoleHandler.level = ALL  
java.util.logging.ConsoleHandler.formatter =  
com.sibvisions.util.log.jdk.JdkLineFormatter  
  
java.util.logging.FileHandler.level = ALL  
java.util.logging.FileHandler.pattern = application_%g.log  
java.util.logging.FileHandler.limit = 10000  
java.util.logging.FileHandler.count = 5  
java.util.logging.FileHandler.formatter =  
com.sibvisions.util.log.jdk.JdkLineFormatter  
  
org.apache.juli.FileHandler.level = ALL  
org.apache.juli.FileHandler.directory = ${catalina.base}/logs  
org.apache.juli.FileHandler.limit = 10000  
org.apache.juli.FileHandler.count = 5  
org.apache.juli.FileHandler.formatter =
```

```
com.sibvisions.util.log.jdk.JdkLineFormatter
org.apache.juli.FileHandler.prefix = application_%g.

#####
#####
# Package specifig log levels
#####
#####

.level = SEVERE

org.restlet.level = OFF
#jvx.rad.util.level = SEVERE

# INFO logs request URL, FINE also logs json, ALL everything
com.sibvisions.rad.server.http.rest.ApplicationResource.level = FINE

# Websocket logging
#com.sibvisions.rad.server.http.rest.WebSocketListener.level = ALL
```

Use **handlers** to define where logged messages will be available.

ConsoleHandler logs messages in console (standard output).  
FileHandler is used for file output.

If you enable logging for **com.sibvisions.rad.server.http.rest.ApplicationResource**, your requests will be logged and it depends on the log level what you'll see. If you set **INFO**, only request URLs will be logged. The level **FINE** also logs json request messages and responses.

From:  
<https://doc.sibvisions.com/> - **Documentation**

Permanent link:  
<https://doc.sibvisions.com/reactui/logging>



Last update: **2024/11/18 10:41**