


Table of Contents

The values for Startup request properties are:

```
osName:      Win32
             MacIntel
             ...
screenWidth: <width> e.g. 1240
screenHeight: <height> e.g. 780

technology:  react
deviceMode:  desktop
deviceType:  Browser
deviceTypeModel: Mozilla/5.0 (Windows NT 10.0; Win64; x64)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/110.0.0.0 Safari/537.36
             Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:109.0)
Gecko/20100101 Firefox/110.0
             Mozilla/5.0 (Windows NT 10.0; Win64; x64)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/110.0.0.0 Safari/537.36
Edg/110.0.1587.46
             Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/109.0.0.0 Safari/537.36
             Mozilla/5.0 (Macintosh; Intel Mac OS X 10.15; rv:109.0)
Gecko/20100101 Firefox/109.0
             Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7)
AppleWebKit/605.1.15 (KHTML, like Gecko) Version/16.3 Safari/605.1.15
             ...
langCode:    <language_code> e.g. en
serverVersion: <supported_server_version> e.g. 2.4.0
timeZone:    <timezone> e.g. Europe/Vienna
locale:      <locale> e.g. en
baseUrl:     <service_url> e.g.
http://www.domain.com/myapp/services/mobile
requestUri:  <browser_url> e.g.
http://www.domain.com/myapp/ui/?language=de
```

From: <https://doc.sibvisions.com/> - **Documentation**

Permanent link: https://doc.sibvisions.com/reactui/startup_props 

Last update: **2023/02/21 08:20**